



## Specifications

Name	EvoPave™ Rubber Interlocking Pavers		
Description	Prefabricated moulded rubber interlocking Pavers composed of recycled rubber particles And MDI polyurethane resin binder		
Dimensions [plan]	200 mm [L] x 160/115 mm [W]		
Thickness	EP 25 mm or EP 45 mm		
Density	± 860 kg/m <sup>3</sup>		
Traction Coefficient	Dry 1.0 [μ]	Wet 1.0 [μ]	Rating : Good
Slip Resistance [μ]	Dry 75 [μ]	Wet 44 [μ]	Rating : Good
Abrasion Resistance 5000 Revs.	0.10 [g]	Rating : Good	[BS 7044]
Fatigue Resistance [New]	No Cracking or Fracture		[BS 7044]
Spike Resistance	Grade 2 – up to 50,000 revs surface repairable Under routine maintenance		[BS 7044]
Resistance to Indentation	0.64 mm	Rating : Good	[BS 7044]
Resistance to Air Ageing	0.18 [g]	Rating : Good	[BS 7044]
Fatigue Resistance [after Air Ageing]	No Cracking or Fracture		[BS 7044]
Resistance to Water Ageing	0.36 [g]	Rating : Good	[BS 7044]
Fatigue Resistance [after Water Ageing]	No Cracking or Fracture		[BS 7044]
Resistance to Artificial Weathering	0.20 [g]	Rating : Good	[BS 7044]
Fatigue Resistance [after Artificial Weathering]	No Cracking or Fracture		[BS 7044]
Resistance to Ozone	No Cracking or Fracture		[BS 7044]
Flammability	Class 1		[DIN 51960]
Infiltration Rate	EP 25 = 180 mm/hr	EP 45 = 285 mm/hr	