Neoflex™ 800 Series
Specification

NEOFLEX FITNESS FLOORING

REPHOUSE

Your supreme floor awaits.

Neoflex™ is prefabricated rubber flooring made of polymerically bound recycled and synthetic rubbers. Available in 20 solid EPDM colors, Neoflex™ 800 Series is ideally suited as a monolithic flooring statement. It is also very popular for borders, highlights and logos in conjunction with our other floors.

Characteristic	Test Method	800 Series
Thickness		3 mm to 10 mm
Roll Width		1.20 m
Density		1,300 kg/m^3
Resilience	DIN 18032-2	40%
Tensile Strength	DIN 18032-2	0.91 N/mm^2
Tear Strength	ASTM D 624	9.7 N/mm
Taber Abrasion	ASTM C 504	0.66 gm
Shore Hardness	ASTM D 2240	60
Remaining Indentation	DIN 53960	0.05 mm
Noise Absorption	EN 21040 / ISO 140	13 dB (4 mm)
Stainability	ASTM D 543-95	
	Alcohol	No Change
	Ammonia	No Change
Coefficient of Friction	ASTM D 2047-97	Dry: 1.10 Wet: 1.03
Slip Resistance	AS/NZS 4586:2004	48 Mean BPM, Class W
Thermal Stability	ASTM C 1026	-40ºC to 100ºC
Flammability	EN 13501	Efl or Bfl-s1
Total VOC	ASTM D 5116	< 0.3 mg/m^2/hr

Standard Colors

801


802

803

804


805


806


807


808

809

810

811


812

813


814

815

816

817

818


819


820

web | www.rephouse.com
email | info@rephouse.com

Our Standard Colors

For real samples, contact us!