




The safe choice for recreation.

Neoflex™ is prefabricated rubber flooring made of polymerically bound recycled and synthetic rubbers. Neoflex™ 500NV Series is soft yet durable. It is composed of 80% EPDM Rubber and 20% Mixed Colored EPDM Rubber, making it an appealing yet very cost effective flooring solution available in a vast variety of colors. It is ideally suited for fitness gyms, changing rooms, waiting rooms, walkways, exhibitions or temporary facilities. It meets European fire and smoke building code regulations.


Characteristic	Test Method	500NV Series
Thickness		3 mm to 10 mm
Roll Width		1.20 m
Density		1,000 kg/m ³
Resilience	DIN 18032-2	49%
Tensile Strength	DIN 18032-2	1.39 N/mm ²
Tear Strength	ASTM D 624	9.7 N/mm
Taber Abrasion	ASTM C 504	0.53 gm
Shore Hardness	ASTM D 2240	60
Remaining Indentation	DIN 53960	0.07 mm
Noise Absorption	EN 21040 / ISO 140	18 dB (10 mm)
Stainability	ASTM D 543-95	
	Alcohol	No Change
	Ammonia	No Change
Coefficient of Friction	ASTM D 2047-97	Dry: 1,10 Wet: 1.03
Slip Resistance	AS/NZS 4586:2004	48 Mean BPM, Class W
Thermal Stability	ASTM C 1026	-40°C to 100°C
Flammability	EN 13501	C _B
Smoke	EN 13501	s1
Total VOC	ASTM D 5116	< 0.3 mg/m ² /hr




Standard Colors




500NV




501NV




502NV




503NV




504NV




505NV




513NV




514NV




515NV




516NV




517NV




518NV




519NV



521NV




524NV



525NV



553NV



554NV

A Small Sampling of our Standard Colors

We have many more... or you can even create your own custom color. Contact us!