

As dynamic as ever. But more economical.


Neoflex™ is prefabricated rubber flooring made of polymerically bound recycled and synthetic rubbers. Neoflex™ Reco Rubber Flooring is a 100% EPDM rubber floor covering - having 75% Recycled EPDM Rubber content. It exhibits the same excellent physical properties of our regular EPDM floors, such as the Neoflex™ 600, 700 and 800 Series Flooring, but with more impressive environmental credentials without the higher costs associated with such floors.

Neoflex™ Reco meets ASTM E648, Class II flammability standards and can therefore be used in most commercial flooring applications as well as of course, sports and recreational uses.


Characteristic	Test Method	Reco Series
Thickness		3 mm to 10 mm
Roll Width		1.20 m
Density		1,200 kg/m ³
Resilience	DIN 18032-2	40%
Tensile Strength	DIN 18032-2	0.91 N/mm ²
Tear Strength	ASTM D 624	9.7 N/mm
Taber Abrasion	ASTM C 504	0.66 gm
Shore Hardness	ASTM D 2240	60
Remaining Indentation	DIN 53960	0.05 mm
Noise Absorption	EN 21040 / ISO 140	13 dB (4 mm)
Stainability	ASTM D 543-95	
	Alcohol	No Change
	Ammonia	No Change
Coefficient of Friction	ASTM D 2047-97	Dry: 1.10 Wet: 1.03
Slip Resistance	AS/NZS 4586:2004	48 Mean BPM, Class W
Thermal Stability	ASTM C 1026	-40°C to 100°C
Flammability	EN 13501	D _n -s2
Total VOC	ASTM D 5116	< 0.3 mg/m ² /hr




Standard Colors




RS 100



RS 101



RS 102




RS 105




RS 107




RS 108



RS 111



RS 112




RL 201




RL 202



RL 204




RL 205




RL 206




RL 208




RL 210




RL 211




RXL 301



RXL 302




RXL 304



RXL 306




RXL 307




RXL 308



RXL 315




RXL 317




RXL 318



RXL 321



RXL 327



RXL 329

A Small Sampling of our Standard Colors

We have many more... or you can even create your own custom color. Contact us!